

12425 Yamaha XSR 900 Seat Cowl 2022> Fitting Instructions

Kit Includes:

1.	X1	12425	XSR 900 Seat Cowl
2.	X2	CWASM60007	M6 x 22mm Rubber Washer
3.	X2	CWASM60004	M6 Flat Plastic Washer
4.	X1	CBRA0207	Included Decals for 12425DZ (Blue Cowl)
4.	X1	CBRA0208	Included Decals for 12425FZ (Black Cowl)
4.	X1	CBRA0212	Included Decals for 12425W (White Cowl)



An instructional video showing how to fit the decals can be found within the product listing description [▶](#)

Please note: The leather handling strap which is fitted to the OEM seat will become obsolete upon fitment of the Pyramid Seat Cowl.

OEM Parts (From the Motorcycle):

5.	X2	OEM XSR 900	M6 x 40mm Dome-Head Screw
----	----	-------------	---------------------------

Assembly Instructions

The Pyramid Seat Cowl for the XSR 900 utilises the existing mounting locations on the seat. You may prefer to remove the seat before fitting the seat cowl, but this is not necessary in order to complete the installation.

- Begin by removing the existing leather strap on the OEM seat. Do this by unscrewing the OEM M6 screw (Item 5). As mentioned above, the leather strap will no longer be required.
- Slide the Pyramid Seat Cowl (Item 1) over the seat. Locate and align the holes and then re-insert the OEM M6 screw (Item 5), together with both rubber washer (Item 2) and plastic washer (Item 3) in the order detailed in 'FIG. 2'.
- Replicate this on the other side. Please do not tighten the screws until the seat cowl is sitting correctly over the seat. Then tighten until sufficient resistance. Overtightening can cause damage to the seat cowl.
- The seat cowl has now been fully fitted, as shown in 'FIG. 1'.

Please Note: We advise that all fixings are checked periodically.



FIG. 1



FIG. 2

Any questions?
sales@pyramidmoto.co.uk
 +44 (0)1427 677990
www.pyramidmoto.co.uk



Follow us on social media and feel free to leave us a review!